



AUTOMATIC SYSTEMS MONITOR



ASM 12-S For Single Engines



ASM 12-T For Twin Engines

Monitors all these areas:

- Low Oil Pressure
- Fire
- High Engine Temperature
- High Bilge Water
- Loss of Cooling Water Flow (or Exhaust Temperature)

This system is completely automatic—no switches to set—just start your engines and go. If one of the systems alarms, the loud bell or optional electronic horn alerts of trouble, and the easy-to-read lighted panel indicates which detector is activated. Even unattended boats get attention when the alarm sounds.

Available for single engine (ASM 12-S) or twin engines (ASM 12-T) and for 12, 24, and 32 volt systems.

Now with MUTE Button. Complete instructions make installation easy. Prevent serious damage to boat and engine, insure peace of mind at all times.

	ASM-12S	ASM-12T
Low oil Pressure	1 (202)	(202)
High Engine Temp Detector	1 (212A)	2 (212A)
Fire Detector	1 (204A)	2 (204A)
Bilge Water Detector	1 (208A)	2 (208A)
Cooling Water Flow Detector	1 (210)	2 (206)
Printed Circuit Control Board	1 (851)	2 (851)
Standard Bell Alarm	1 (RBA-12)	1 (RBA-12)
Visual Indicator Panel	1 (852)	1 (853)
Interconnecting Cable	10'	10' x2